



# Wrangler® 2625 DB

26-Inch Automatic Scrubber



The Wrangler 2625 DB is the mid-size value leader with its large scrubber features and compact, maneuverable package.

- The 25-gal. solution and 27-gal. recovery tanks on the Wrangler 2625 DB are 25 percent larger than tanks on comparable mid-sized scrubbers. This translates to fewer trips to empty and refill the machine.
- The compact body with front drive wheels and rear casters let the Wrangler 2625 DB turn with ease, even in constricted areas.
- Three scrub pressures allow the Wrangler 2625 DB to take on any scrubbing task.
- Variable-speed wheel-drive assures smooth operation, reducing operator fatigue and maintaining productivity throughout the shift.
- Rugged 7-gauge steel frame and durable polyethylene body withstand heavy-duty commercial use.
- The on-board battery charger allows safe, convenient battery charging anywhere an outlet is available.
- Straight, long-lasting urethane squeegee picks up equally well in forward and reverse.
- The Wrangler 2625 DB is available with a curved squeegee (#2492499), an ideal option for industrial applications. This attachment funnels water and debris to the center of the squeegee for easy recovery.

**NSS® Enterprises, Inc.**  
3115 Frenchmens Road  
Toledo, Ohio 43607-2958  
USA  
[www.nss.com](http://www.nss.com)



Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

# Wrangler 2625 DB Specifications

## Brush/Pad

Cleaning Path	25 in (64 cm)
Motor	2 permanent magnet, gear drive
Voltage	24V
HP	0.75 HP
Speed	270 RPM
Pressure	60 lbs (27 kg), 90 lbs (40 kg), 120 lbs (54 kg)
Pad Drivers	Two 13 in (33 cm) poly back tufted with retaining cup

## Vacuum Motor

Type	3-stage, bypass, tangential discharge
Voltage	24V
HP	0.75 HP
Waterlift	56 in (142 cm)

## Drive System

Type	Wheel-drive transaxle
Voltage	24V
HP	0.33 HP
Speed	Forward 200 ft/min (61 M), reverse 125 ft/min (38 m)

## Construction

Tank (Solution)	Rotocast polyethylene 25 gal (95 l)
Tank (Recovery)	Rotocast Polyethylene 27 gal (102 l)
Frame	7-gage steel
Caster	One 4 in (10 cm) ball bearing swivel caster
Wheels	Two 8 in (20 cm) x 2 in (5 cm) non-marking, slip-grip tread

**Batteries** Four 6V batteries, 225 AH

## Switches & Controls

Master	On/off
Propulsion	Twist grip drive control
Solution	Manual at handle bar through rigid actuators; adjustable flow, forged brass valve, celcon rotor, o-ring seal. Solenoid prevents solution flow when brushes are not moving.

**Squeegee** 32 in (81 cm) swing type with breakaway feature. Optional 35 in (89 cm) curved squeegee available

**Sound Level** 68 dBA

## Dimensions

Length	55.5 in (141 cm)
Width	27 in (69 cm)
Height	41 in (104 cm)

**Weight (Machine)** 608 lbs (276 kg)  
(Shipping) 717 lbs (326 kg)

**Shipping Class** 70

**Warranty** 3 year limited, 10 year poly parts, 3 year transaxle

**Productivity** 25,999 sq ft per hour (2,415 sq m)  
90,966 sq ft per charge (8,451 sq m)



- 1 The percolator breaks down foam, protecting the vac motor from damage.
- 2 A solenoid valve near the brush head prevents solution flow when the brushes are not moving.
- 3 An hour meter helps track regular maintenance tasks.
- 4 The 32-in. squeegee swings wide on turns to leave the floor drier. The breakaway feature prevents damage if the squeegee catches on an object.
- 5 The clear solution tank hose indicates the amount of cleaning solution remaining, and allows easy draining of the solution tank.
- 6 On-board battery charger recharges anywhere an outlet is available.
- 7 Twist-grip handles let the operator easily control the variable-speed propulsion system.
- 8 The float shut-off protects the vacuum motor from liquid or foam damage.



Adjustable solution flow allows chemical and water conservation, using only what is needed to clean the floor.

Twister approval means stone and concrete floors can be scrubbed without harmful chemicals, protecting the environment.

DISTRIBUTED BY



**NSS Enterprises, Inc.**  
3115 Frenchmens Road  
Toledo, OH 43607-2958  
USA

P: (800) 677-1663  
F: (419) 531-3761

mailus@nss.com  
www.nss.com

Specifications subject to change without notice.

Printed in USA

©2008 NSS Enterprises, Inc.

#9092601 REV D 11/08